


PIM22 33.8x42.5 (PRESS FIT) CASE 180BX **ISSUE A**


DATE 20 AUG 2021

NOTES:

- 1. CONTROLLING DIMENSION: MILLIMETERS
- 2. PIN POSITION TOLERANCE IS ± 0.4mm

	MILLIMETERS			
DIM	MIN.	NOM.	MAX.	
Α	11.65	12.00	12.35	
A1	16.00	16.50	17.00	
A2	0.00	0.35	0.60	
A3	12.85	13.35	13.85	
b	1.15	1.20	1.25	
b1	0.59	0.64	0.69	
D	33.50	33.80	34.10	
D1	4.40	4.50	4.60	
D2	27.95	28.10	28.25	
E	47.70	48.00	48.30	
E1	42.35	42.50	42.65	
E2	52.90	53.00	53.10	
E3	62.30	62.80	63.30	
E4	4.90	5.00	5.10	
P	2.20	2.30	2.40	





12.8 12.8 9.6 9.6 Ø0.94~1.09 PLATED THRU HOLE

14.05

14.05

RECOMMENDED MOUNTING PATTERN

Ø9.0

GENERIC MARKING DIAGRAM*

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	
--	--

FRONTSIDE MARKING

2D CODE

BACKSIDE MARKING

XXXXX = Specific Device Code

= Assembly & Test Site Code

YYWW = Year and Work Week Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot " • ", may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	98AON19724H	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.		
DESCRIPTION:	PIM22 33.8x42.5 (PRESS FIT)		PAGE 1 OF 1	

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves brisefin and of 160 m are trademarked so defined values of services and of the confined values and of the values of the confined values and of the values of the confined values and of the values of the v special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.