



А





FRONT VIEW



BOTTOM VIEW


SOD-123FA CASE 425AB ISSUE A

DATE 11 AUG 2022

NDTES

- 1. NO INDUSTRY STANDARD APPLIES TO THIS PACKAGE.
- 2. ALL DIMENSIONS ARE IN MILLIMETERS.
- 3. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH AND THE BAR PROTRUSIONS.

DIM	MILLIMETERS			
	MIN.	NDM.	MAX.	
A	1.23	1.33	1.43	
b	0,80	1.00	1.20	
C	0.16	0.23	0.30	
D	2.70	2,80	2.90	
D1	3.40	3,60	3.80	
E	1.70	1.80	1.90	
He	2.45		2.60	
L	0.35	0.60	0.85	



MOUNTING FOOTPRINT*

* For additional information on our Pb-Free strategy and soldering details, please download the DN Semiconductor Soldering and Mounting Techniques Reference Manual, SDLDERRM/D.

DOCUMENT NUMBER:	98AON13722G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.		
DESCRIPTION:	SOD-123FA		PAGE 1 OF 1	

onsemi and ONSEMi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product rights nor the rights of others.