

0.10

0.05

Ф

BOTTOM VIEW

CAB

C NOTE 3

DATE 19 FEB 2010

- DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
- Y14.5M, 1994.
 CONTROLLING DIMENSION: MILLIMETERS.
 DIMENSION b APPLIES TO PLATED TERMINAL
 AND IS MEASURED BETWEEN 0.15 AND 0.30 MM
 FROM TERMINAL TIP.
 COPLANARITY APPLIES TO THE EXPOSED PAD
 AS WELL AS THE TERMINALS.

	MILLIMETERS		
DIM	MIN	MAX	
Α	0.80	1.00	
A1		0.05	
А3	0.20 REF		
b	0.20	0.30	
D	4.00 BSC		
D2	2.60	2.80	
E	4.00 BSC		
E2	2.60	2.80	
е	0.50 BSC		
K	0.20		
L	0.35	0.45	
L1	0.00	0.15	

GENERIC MARKING DIAGRAM*



XXXXX = Specific Device Code


= Assembly Location

= Wafer Lot L = Year W = Work Week = Pb-Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G", may or not be present.

MOUNTING FOOTPRINT



DOCUMENT NUMBER:	98AON48317E Electronic versions are uncontrolled except when accessed directly from the Document Repositor Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.		
DESCRIPTION:	QFN20 4X4, 0.5P		PAGE 1 OF 1

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.