



DATE 02 MAY 2017

- NOTES:
 1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
 CONTROLLING DIMENSION: MILLIMETERS.
- CONTHOLLING DIMENSION: MILLIMETERS.
 DIMENSION & APPLIES TO PLATED
 TERMINAL AND IS MEASURED BETWEEN
 0.20 AND 0.25 MM FROM THE TERMINAL TIP.
 COPLANARITY APPLIES TO THE EXPOSED
 PAD AS WELL AS THE PLATED TERMINALS.

	MILLIMETERS			
DIM	MIN	NOM	MAX	
Α	0.30	0.35	0.40	
A1			0.05	
b	0.12	0.17	0.22	
D	3.00	3.10	3.20	
D1	1.80	1.90	2.00	
Е	4.20	4.30	4.40	
E1	3.00	3.10	3.20	
е	0.40 BSC			
K	0.35 REF			
L	0.20	0.25	0.30	
L1	0.05 REF			

GENERIC MARKING DIAGRAM*



XXXXX = Specific Device Code

= Assembly Location

ı = Wafer Lot Υ = Year = Work Week W = Pb-Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot " •", may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	98AON63532G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	X2QFN34 3.1X4.3, 0.4P		PAGE 1 OF 1

onsemi and Onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries, onsemi reserves brisefin and of 160 m are trademarked to demonstrate the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

0.40-**PITCH**

34X 0.22

DIMENSIONS: MILLIMETERS