





NOTES:

- 1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M. 2018.
- CONTROLLING DIMENSION: MILLIMETER
- 3. POWER INIDCATOR
- 4. HIROSE 12 PIN CONNECTOR
- 5. GigE CONNECTOR6. M3X0.5 DEPTH ▼ 3.0
- 7. 1/4-20 UNC DEPTH $\sqrt{5.08}$

DIM	MIN.	NOM.	MAX.		
D	96.00	96.20	96.40		
D1	93.00	93.20	93.40		
Е	59.03	61.00	61.13		
А	59.03	61.00	61.13		
G1	30.35	30.48	30.61		
G2	30.35	30.48	30.61		
G3	30.47	30.60	30.73		
q	38.98	39.11	39.24		
q1	19.37	19.50	19.63		

DOCUMENT NUMBER:	98AON65071H	Electronic versions are uncontrolled except when accessed directly from Printed versions are uncontrolled except when stamped "CONTROLLED (
DESCRIPTION:	CMOD 96.20x61.00x61.00		PAGE 1 OF 1

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves onsem and of 15GTI in are trademarks of Semiconductor Components industries, LLC due onsem or its substitutines in the Office States and/or other countries. Onsem reserves the right to make changes without further notice to any products herein. onsem makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.