

产品概览

MURA260T3: 功率整流器，Ultrafast 恢复，2 A，600 V

欲看完整文档，请参阅数据表。

该 Ultrafast 功率整流器适用于高电压、高频率整流，或者适合作为表面贴装应用中的续流和保护二极管，在此类应用中紧凑的尺寸和重量至关重要。

特性

- Small Compact Surface Mountable Package with J-Bend Leads
- Rectangular Package for Automated Handling
- High Temperature Glass Passivated Junction
- Low Forward Voltage Drop (1.2 Volts Max @ 2.0 A, T_J = 150°C)
- Case: Epoxy, Molded
- Weight: 70 mg (approximately)
- Finish: All External Surfaces Corrosion Resistant and Terminal Leads are Readily Solderable
- Lead and Mounting Surface Temperature for Soldering Purposes: 260°C Max. for 10 Seconds
- Shipped in 12 mm Tape and Reel, 5000 units per reel
- Polarity: Polarity Band Indicates Cathode Lead

For more features, see the data sheet

器件电气规格

产品	Pricing (\$/Unit)	Compliance	Status	Type	I _{O(rec)} Max (A)	t _{rr} Max (ns)	V _{RRM} Max (V)	V _{FM} Max (V)	I _{FSM} Max (A)	I _R Max (mA)	Package Type
MURA260T3G	0.1133	Pb-free Halide free non AEC-Q and PPAP	Active	Ultrafast	2	75	600	1.45	35	0.005	SMA-2

欲了解更多信息，请联系您当地的销售支援 www.onsemi.cn。

创建于：9/21/2021