

产品概览

DTC143ZE: NPN Bipolar Digital Transistor (BRT)

欲看完整文档，请参阅数据表。

This series of digital transistors is designed to replace a single device and its external resistor bias network. The Bias Resistor Transistor (BRT) contains a single transistor with a monolithic bias network consisting of two resistors; a series base resistor and a base-emitter resistor. The BRT eliminates these individual components by integrating them into a single device. The use of a BRT can reduce both system cost and board space.

特性

- Simplifies Circuit Design
- Reduces Board Space
- Reduces Component Count
- NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AECQ101 Qualified and PPAP Capable
- These Devices are PbFree, Halogen Free/BFR Free and are RoHS Compliant

器件电气规格

产品	Compliance	Status	Polarity	I_C Continuous (A)	V_{BRICE0} Min (V)	h_{FE} Min	R1 (k Ω)	R2 (k Ω)	R1/R2 Typ	$V_{i(off)}$ Max (V)	$V_{i(on)}$ Min (V)	Package Type
DTC143ZET1G	Pb-free Halide free	Active	NPN	0.1	50	80	4.7	47	0.1	0.5	1.3	SC-75-3
NSVDTC143ZET1G	AEC Qualified PPAP Capable Pb-free Halide free	Active	NPN	0.1	50	80	4.7	47	0.1	0.5	1.3	SC-75-3

欲了解更多信息，请联系您当地的销售支援 www.onsemi.cn。

创建于：8/22/2019