

## 产品概览

### UMC2: Complementary Bipolar Digital Transistor (BRT)

欲看完整文档，请参阅数据表。

The Dual PNP Bipolar Digital Transistor contains a single transistor with a monolithic bias network consisting of two resistors: a series base resistor and a base-emitter resistor. These digital transistors are designed to replace a single device and its external resistor bias network. The Dual PNP Bipolar Digital Transistor eliminates these individual components by integrating them into a single device. In the UMC2NT1 series, two devices are housed in the SOT-353 package which is ideal for low power surface mount applications where board space is at a premium.

### 特性

- Simplifies Circuit Design
- Reduces Board Space
- Reduces Component Count
- Available in 8 mm, 7 inch/3000 Unit Tape and Reel.
- Pb-Free Packages are Available
- NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable

### 器件电气规格

产品	Compliance	Status	Polarity	$I_C$ Continuous (A)	$V_{(BR)CEO}$ Min (V)	$h_{FE}$ Min	R1 (k $\Omega$ )	R2 (k $\Omega$ )	R1/R2 Typ	$V_{(i(off))}$ Max (V)	$V_{(i(on))}$ Min (V)	Package Type
NSVUMC2NT1G	AEC Qualified PPAP Capable Pb-free Halide free	Active	Complementary	0.1	50	60	22	22	1	-	-	SC-88A / SC-70-5

欲了解更多信息，请联系您当地的销售支援 [www.onsemi.cn](http://www.onsemi.cn)。

创建于：8/17/2019