

## 产品概览

### MUR120: 功率整流器，超快速恢复，开关模式，1 A，200 V

欲看完整文档，请参阅数据表。

超快整流器适用于开关电源、逆变器和续流二极管。

#### 特性

- Ultrafast 25, 50 and 75 Nanosecond Recovery Times
- 175°C Operating Junction Temperature
- Low Forward Voltage
- Low Leakage Current
- High Temperature Glass Passivated Junction
- Reverse Voltage to 600 Volts
- Mechanical Characteristics:
  - Case: Epoxy, Molded
  - Weight: 0.4 gram (approximately)
  - Finish: All External Surfaces Corrosion Resistant and Terminal Leads are Readily Solderable
  - Lead Temperature for Soldering Purposes: 260°C Max. for 10 Seconds

For more features, see the data sheet

#### 器件电气规格

产品	Pricing (\$/Unit)	Compliance	Status	Type	$I_{O(rec)}$ Max (A)	$t_{rr}$ Max (ns)	$V_{RRM}$ Max (V)	$V_{FM}$ Max (V)	$I_{FSM}$ Max (A)	$I_R$ Max (mA)	Package Type
MUR120G	0.0749	Pb-free Halide free non AEC-Q and PPAP	Active	Ultrafast	1	35	200	0.875	35	0.002	Axial Lead-2
MUR120RLG	0.0741	Pb-free Halide free non AEC-Q and PPAP	Active	Ultrafast	1	35	200	0.875	35	0.002	Axial Lead-2

欲了解更多信息，请联系您当地的销售支援 [www.onsemi.cn](http://www.onsemi.cn)。

创建于：9/29/2020