

产品概览

BZX84C15L: 250 mW , 15 V \pm 5% 齐纳二极管稳压器

欲看完整文档，请参阅数据表。

此齐纳二极管系列采用方便的表面贴装塑料 SOT-23 封装。此类器件提供稳压功能，且空间要求极低。此类器件非常适用于蜂窝电话、手持便携设备和高密度 PC 主板等应用。

特性

- 250 mW Rating on FR-4 or FR-5 Board
- Zener Breakdown Voltage Range - 2.4 V to 75 V
- Package Designed for Optimal Automated Board Assembly
- Small Package Size for High Density Applications
- ESD Rating of Class 3 (>16 KV) per Human Body Model
- Mechanical Characteristics:
- CASE: Void-free, transfer-molded, thermosetting plastic case
- FINISH: Corrosion resistant finish, easily solderable
- MAXIMUM CASE TEMPERATURE FOR SOLDERING PURPOSES: 260°C for 10 Seconds
- POLARITY: Cathode indicated by polarity band

For more features, see the data sheet

器件电气规格

产品	Pricing (\$/Unit)	Compliance	Status	V _Z Typ (V)	P Max (W)	Package Type
BZX84C15LT1G	0.014	Pb-free Halide free	Active	15	0.225	SOT-23-3
BZX84C15LT3G	0.014	Pb-free Halide free	Active	15	0.225	SOT-23-3
SZBZX84C15LT1G	0.0165	AEC Qualified PPAP Capable Pb-free Halide free	Active	15	0.225	SOT-23-3
SZBZX84C15LT3G	0.0165	AEC Qualified PPAP Capable Pb-free Halide free	Active	15	0.225	SOT-23-3

欲了解更多信息，请联系您当地的销售支援 www.onsemi.cn。

创建于：7/14/2020