

产品概览

BZX84C39L: 250 mW 39 V $\pm 5\%$ Zener Diode Voltage Regulator

欲看完整文档，请参阅数据表。

This series of Zener diodes is offered in the convenient, surface mount plastic SOT-23 package. These devices are designed to provide voltage regulation with minimum space requirement. They are well suited for applications such as cellular phones, hand held portables, and high density PC boards.

特性

- 250 mW Rating on FR-4 or FR-5 Board
- Zener Breakdown Voltage Range - 2.4 V to 75 V
- Package Designed for Optimal Automated Board Assembly
- Small Package Size for High Density Applications
- ESD Rating of Class 3 (>16 KV) per Human Body Model
- Mechanical Characteristics:
- CASE: Void-free, transfer-molded, thermosetting plastic case
- FINISH: Corrosion resistant finish, easily solderable
- MAXIMUM CASE TEMPERATURE FOR SOLDERING PURPOSES: 260°C for 10 Seconds
- POLARITY: Cathode indicated by polarity band

For more features, see the data sheet

器件电气规格

产品	Pricing (\$/Unit)	Compliance	Status	V _Z Typ (V)	P Max (W)	Package Type
BZX84C39LT1G	0.014	Pb-free Halide free	Active	39	0.225	SOT-23-3

欲了解更多信息，请联系您当地的销售支援 www.onsemi.cn。

创建于：1/20/2020