

产品概览

MMSZ22: 500 mW , 22 V \pm 5% 齐纳二极管稳压器

欲看完整文档，请参阅数据表。

三个完整齐纳二极管系列采用方便的表面贴装塑料 SOD-123 封装。此类器件是无引线 34 封装样式的方便替代产品。

特性

- 500 mW Rating on FR-4 or FR-5 Board
- Wide Zener Reverse Voltage Range - 2.4 V to 56 V
- Package Designed for Optimal Automated Board Assembly
- Small Package Size for High Density Applications
- ESD Rating of Class 3 (exceeding 16 kV) per the Human Body Model
- CASE: Void-free, transfer-molded, thermosetting plastic case
- FINISH: Corrosion resistant finish, easily solderable
- MAXIMUM CASE TEMPERATURE FOR SOLDERING PURPOSES: 260°C for 10 Seconds
- POLARITY: Cathode indicated by polarity band
- FLAMMABILITY RATING: UL94 V-0

For more features, see the data sheet

器件电气规格

产品	Pricing (\$/Unit)	Compliance	Status	V _Z Typ (V)	P Max (W)	Package Type
MMSZ22T1G	0.0247	Pb-free Halide free	Active	22	0.5	SOD-123
SZMMSZ22T1G	0.0612	AEC Qualified PPAP Capable Pb-free Halide free	Active	22	0.5	SOD-123

欲了解更多信息，请联系您当地的销售支援 www.onsemi.cn。

创建于：4/6/2020