

产品概览

CAT24C04: EEPROM Serial 4-Kb I²C

欲看完整文档，请参阅数据表。

The CAT24C04 is a EEPROM Serial 2-Kb I2C device organized internally as 32 pages of 16 bytes each. This device support both the Standard (100 kHz) as well as Fast (400 kHz) I2C protocol. Data is written by providing a starting address, then loading 1 to 16 contiguous bytes into a Page Write Buffer, and then writing all data to non-volatile memory in one internal write cycle. Data is read by providing a starting address and then shifting out data serially while automatically incrementing the internal address count. External address pins make it possible to address up to four CAT24C04 devices on the same bus.

特性

- Supports Standard and Fast I2C Protocol
 - 1.7 V to 5.5 V Supply Voltage Range
 - 16-Byte Page Write Buffer
 - Hardware Write Protection for Entire Memory
 - Schmitt Triggers and Noise Suppression Filters on I2C Bus Inputs (SCL and SDA)
 - Low Power CMOS technology
 - More than 1,000,000 program/erase cycles
 - 100 year data retention
 - Industrial Temperature Range
 - 8-lead SOIC and TSSOP, WLCS P 4 and 5-ball, 8-pad UDFN and 5-lead TSOT-23 packages
- For more features, see the data sheet

应用

- Alarm Systems
- Audio Players
- Automotive Systems
- Cable Modems
- CDRW

器件电气规格

产品	Compliance	Status	Type	Density	Organization	Data Transmission Standard	f _{cycle} Max (kHz)	t _{ACC} Max ns	V _{CC} Min (V)	V _{CC} Max (V)	I _{standby} Max (μA)	I _{act} Max (mA)	T Min (°C)	T Max (°C)	Package Type
CAT24C04C4ATR	Pb-free Halide free	Active	Serial	4 kb	512 x 8	I2C	400	-	1.7	5.5	1	1	-40	85	WLCS P-4
CAT24C04C5ATR	Pb-free Halide free	Active	Serial	4 kb	512 x 8	I2C	400	-	1.7	5.5	1	1	-40	85	WLCS P-5
CAT24C04HU4I-GT3	Pb-free Halide free	Active	Serial	4 kb	512 x 8	I2C	400	-	1.7	5.5	1	1	-40	85	UDFN-8
CAT24C04TDI-GT3	Pb-free Halide free	Active	Serial	4 kb	512 x 8	I2C	400	-	1.7	5.5	1	1	-40	85	TSOT-23-5
CAT24C04WI-GT3	Pb-free Halide free	Active	Serial	4 kb	512 x 8	I2C	400	-	1.7	5.5	1	1	-40	85	SOIC-8
CAT24C04YI-GT3	Pb-free Halide free	Active	Serial	4 kb	512 x 8	I2C	400	-	1.7	5.5	1	1	-40	85	TSSOP-8

欲了解更多信息，请联系您当地的销售支援 www.onsemi.cn。

创建于：8/19/2019