

产品概览

LP2951: LDO Regulator, 100 mA, 30V, Micropower, with Shutdown

欲看完整文档，请参阅数据表。

The LP2950 and LP2951 are micropower low dropout (LDO) linear voltage regulators that are specifically designed to maintain proper regulation with an extremely low input-to-output voltage differential. These devices feature a very low quiescent bias current of 75 μ A and are capable of supplying output currents in excess of 100 mA. Internal current and thermal limiting protection is provided. The LP2951 LDO linear voltage regulator has three additional features. The first is the Errorbar Output that can be used to signal external circuitry of an out of regulation condition, or as a microprocessor power-on reset. The second feature allows the output voltage to be preset to 5.0 V, 3.3 V or 3.0 V output (depending on the version) or programmed from 1.25 V to 29 V. It consists of a pinned out resistor divider along with direct access to the Error Amplifier feedback input. The third feature is a Shutdown input that allows a logic level signal to turn-off or turn-on the regulator output. Due to the low input-to-output voltage differential and bias current specifications, these devices are ideally suited for battery powered computer, consumer, and industrial equipment where an extension of useful battery life is desirable. The LP2950 is available in the three pin case 29 and DPAK packages, and the LP2951 is available in the eight pin dual-in-line, SO-8 and Micro-8 surface mount packages. The 'A' suffix devices feature an initial output voltage tolerance $\pm 0.5\%$.

特性

- Wide Input Range: Up to 30 V
 - Rated Output Current of 100 mA
 - Low Dropout 50 mV at 100 mA and 380 mV at 100 mA
 - Low Quiescent Current: 75 μ A (Typ)
 - Requires Only a 1.0 mF Output Capacitor for Stability
 - Internal Current and Thermal Limiting
 - LP2951 also has Error(bar) Output Signals an Out of Regulation Condition
 - LP2951 also has Output Programmable from 1.25 V to 29 V
 - LP2951 also has Logic Level Shutdown Input
 - Extremely Tight Line and Load Regulation
- For more features, see the data sheet

应用

- Automotive
- Avionics: RADAR

优势

- Enables use with 24V rail
- Sufficient power capability for MCU
- Lower thermal impact than Vreg
- Longer battery life
- Small size, low cost system
- Built-in protection features
- Enhanced protection capability
- Flexibility for various end product applications
- Enhanced protection capability
- Accurate system level design capability

终端产品

- AC Analog Input Module
- Logistics Robot CPU Board
- Optical Line Card

器件电气规格

产品	Pricing (\$/Unit)	Compliance	Status	Output	Polarity	V _O (V)	I _O Typ (A)	V _I Min (V)	V _I Max (V)	V _{DO} Typ (V)	I _q Typ (mA)	PSR R (dB)	Noise (μV _{rms})	Enable	PowerGood	Package Type
LP2951ACD-3.0G	0.2219	Pb-free Halide free	Active	Single	Positive	3	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	SOIC-8
LP2951ACD-3.0R2G	0.2091	Pb-free Halide free	Active	Single	Positive	3	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	SOIC-8
LP2951ACD-3.3G	0.2583	Pb-free Halide free	Active	Single	Positive	3.3	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	SOIC-8
LP2951ACD-3.3R2G	0.2207	Pb-free Halide free	Active	Single	Positive	3.3	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	SOIC-8
LP2951ACDM-3.0RG	0.2933	Pb-free Halide free	Active	Single	Positive	3	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	Micro8™
LP2951ACDM-3.3RG	0.2483	Pb-free Halide free	Active	Single	Positive	3.3	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	Micro8™
LP2951ACDMR2G	0.2691	Pb-free Halide free	Active	Single	Positive	Adj	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	Micro8™
LP2951ACDR2G	0.2005	Pb-free Halide free	Active	Single	Positive	Adj	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	SOIC-8
LP2951ACN-3.0G	0.3	Pb-free Halide free	Active	Single	Positive	3	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	PDIP-8
LP2951ACN-3.3G	0.3477	Pb-free Halide free	Active	Single	Positive	3.3	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	PDIP-8
LP2951ACNG	0.2768	Pb-free Halide free	Active	Single	Positive	Adj	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	PDIP-8
LP2951CD-3.0G	0.2035	Pb-free Halide free	Active	Single	Positive	3	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	SOIC-8
LP2951CD-3.0R2G	0.2035	Pb-free Halide free	Active	Single	Positive	3	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	SOIC-8
LP2951CD-3.3G	0.1989	Pb-free Halide free	Active	Single	Positive	Adj	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	SOIC-8
LP2951CD-3.3R2G	0.1731	Pb-free Halide free	Active	Single	Positive	3.3	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	SOIC-8
LP2951CDM-3.0R2G	0.2632	Pb-free Halide free	Active	Single	Positive	3	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	Micro8™
LP2951CDM-3.3R2G	0.29	Pb-free Halide free	Active	Single	Positive	3.3	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	Micro8™
LP2951CDMR2G	0.29	Pb-free Halide free	Active	Single	Positive	Adj	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	Micro8™
LP2951CDR2G	0.1621	Pb-free Halide free	Active	Single	Positive	Adj	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	SOIC-8
LP2951CN-3.0G		Pb-free Halide free	Active	Single	Positive	3	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	PDIP-8
LP2951CN-3.3G	0.2572	Pb-free Halide free	Active	Single	Positive	Adj	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	PDIP-8
LP2951CNG	0.2512	Pb-free Halide free	Active	Single	Positive	Adj	0.1	2.3	30	0.35	0.093	48	56	Yes	Yes	PDIP-8

欲了解更多信息，请联系您当地的销售支援 www.onsemi.cn。

创建于：1/20/2020