

产品概览

MC74AC14: Hex Inverter with Schmitt Trigger Input

欲看完整文档，请参阅数据表。

The MC74AC14/74ACT14 contains six logic inverters which accept standard CMOS Input signals (TTL levels for MC74ACT14) and provide standard CMOS output levels. They are capable of transforming slowly changing input signals into sharply defined, jitter-free output signals. In addition, they have a greater noise margin than conventional inverters. The MC74AC14/74ACT14 has hysteresis between the positive-going and negative-going input thresholds (typically 1.0 V) which is determined internally by transistor ratios and is essentially insensitive to temperature and supply voltage variations.

特性

- Schmitt Trigger Inputs
- Outputs Source/Sink 24 mA
- ACT14 Has TTL Compatible Inputs
- Pb-Free Packages are Available

器件电气规格

产品	Pricing (\$/Unit)	Compliance	Status	Type	Channels	V _{CC} Min (V)	V _{CC} Max (V)	t _{pd} Max (ns)	I _O Max (mA)	Package Type
MC74AC14DG	0.1735	Pb-free Halide free	Active	Inverter	6	2	6	7	24	SOIC-14
MC74AC14DR2G	0.16	Pb-free Halide free	Active	Inverter	6	2	6	7	24	SOIC-14
MC74AC14DTR2G	0.1911	Pb-free Halide free	Active	Inverter	6	2	6	7	24	TSSOP-14
NLV74AC14DR2G	0.2	AEC Qualified PPAP Capable Pb-free Halide free	Active	Inverter	6	2	6	7	24	SOIC-14
NLV74AC14DTR2G	0.1911	AEC Qualified PPAP Capable Pb-free Halide free	Active	Inverter	6	2	6	7	24	TSSOP-14
NLVACT14DR2G	0.2787	AEC Qualified Pb-free Halide free	Active	Inverter	6	4.5	5.5	7	24	SOIC-14

欲了解更多信息，请联系您当地的销售支援 www.onsemi.cn。

创建于：3/29/2020