PIN 1


INDICATOR

2x 0.20 C

// 0.10 C

□ 0.05 C

2x 0.20 C



TOP VIEW


SIDE VIEW


DATE 28 JAN 2014

NOTES:

- ASME Y14.5M, 1994.

	MILLIMETERS		
DIM	MIN.	MAX.	
Α		0.85	
A1	-	0.05	
b	0.15	0.25	
D	5.00	BSC	
E	5.00	BSC	
е	0.40	BSC	
L	0.30	0.40	





RECOMMENDED MOUNTING FOOTPRINT

SEATING PLANE

В

D

- 1. DIMENSIONING AND TOLERANCING PER.
- CONTROLLING DIMENSION: MILLIMETERS

	31	-40X b -40X b
חדדם	NA \ / T \ /	

BUIIUM VIEW

GENERIC MARKING DIAGRAM*



XXXXX = Specific Device Code Y = Year

M = MonthDDD = Additional Traceability Data



XXXXX = Specific Device Code Y = Year

DD = Additional Traceability Data

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot " ■", may or may not be present.

DOCUMENT NUMBER:	98AON78688E	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	VQLP40 5X5, 0.5P		PAGE 1 OF 1

ON Semiconductor and (III) are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.