

Factory Automation Lens Options AND90062/D

INTRODUCTION

The following application note includes a list of lenses that has been found working well with the listed image sensors from **onsemi**. This information is provided as a general guide line for lens use in a general Factory Automation application; we recommend the user to perform his own evaluation to determine which lens is suitable for the application.

LENS LIST

Image sensor: XGS 16000, Optical format 1.1'

Tested Lenses

	Part Number	FL (mm)	Measured Parameter		
Lens Maker			MTF (cy/mm)	Veiling Glare (%)	Max Optical Distortion (%)
Fujinon	CF35-ZA-1S	35	140	1.0	4 (Note 1)
Fujinon	CF16-ZA-1S	16	140	1.0	-9.4 (Note 1)
Kowa	LM12FC	12	144	2.26	-3.851
Kowa	LM35FC	35	124	2.13	0.963

NOTE: MTF: 20% signal drop at the center of the image, f/#:4

Veiling Glare: a sort of contrast measure, the lower the better

Distortion: is computed as the ratio of the error in the radial distance of an image point from the ideal position in percent

1. Equivalent to geometric distortion.

AND90062/D

onsemi, ONSEMI, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "onsemi" or its affiliates and/or subsidiaries in the United States and/or other countries. onsemi owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of onsemi's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. onsemi reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and onsemi makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at

www.onsemi.com/support/sales